



ST35 - ST52 Low Pressure Pipe Hydraulic Cylinder Honed Tube For Fluid Transport

Our Product Introduction

for more products please visit us on pipesteels.com

Basic Information

- Place of Origin: China
- Brand Name: Zhengshen
- Certification: ISO, GOST, CE
- Minimum Order Quantity: 1 T
- Price: Negotiable
- Packaging Details: Bundle
- Delivery Time: 5-15 days
- Payment Terms: T/T, LC



Product Specification

- Highlight: ST35 low pressure pipe, ST52 low pressure pipe, 15mm hydraulic cylinder honed tube



More Images



Product Description

ST35-ST52 Low-pressure Fluid Transport Honed Seamless Steel Pipe

Feature:

The seamless steel pipe is made of perforated whole round steel, and the steel pipe without weld seam on the surface is called seamless steel pipe.

According to the production method, seamless steel pipes can be divided into hot-rolled seamless steel pipes, cold-rolled seamless steel pipes, cold-drawn seamless steel pipes, extruded seamless steel pipes, and pipe jacking. According to the cross-sectional shape, the seamless steel pipe is divided into two types: round and special-shaped. The maximum diameter is 900mm and the minimum diameter is 4mm. According to different uses, there are thick-walled seamless steel pipes and thin-walled seamless steel pipes.

Seamless steel pipes are mainly used as petroleum geological drilling pipes, cracking pipes for petrochemical industries, boiler pipes, bearing pipes and high-precision structural steel pipes for automobiles, tractors, and aviation.

Specification:

| | |
|---------------|--|
| Application | OIL PIPE, Low-pressure fluid transport, construction, fence posts, and conduit |
| Alloy Or Not | Non-Alloy |
| Section Shape | Round |
| Special Pipe | Thick Wall Pipe |

| | |
|---------------------------|---|
| Outer Diameter | 13.7 - 610 mm, DN8-DN600 |
| Thickness | 1.3 - 15 mm |
| Standard | API, ASTM, bs, DIN, GB, JIS, ASTM A53, ASTM A106, API 5L and so on, API 5L, ASTM A53-2007, BS 1387, BS EN10025, BS EN 39, BS EN10219, DIN EN 10217-1-2005, DIN 2444, DIN EN 10025, GB/T 9711.1-1997, GB/T 3091-2001, JIS G3444-2006 |
| Grade | 45#, Q235, Q345, Q195, ST37, ST52, ST42, 10#-45#, Q195-Q345, ST35-ST52 |
| Tolerance | ±10% |
| Processing Service | Punching, Cutting |
| Secondary Or Not | Non-secondary |
| Commodity | Black Carbon Steel Seamless Pipe for oil and gas |
| Wall Thickness | 1.3mm-30.0mm (sch40/ sch80/ sch160) |
| Length | 6m/5.8m or customized |
| Material | Q195, Q235, Q345, #20 |
| pipe ends | bevel ends or plain ends with caps |
| Technique | Hot Rolled |
| Certification | API |
| Type | Seamless Steel Pipe |


The main production process of hot-rolled seamless steel pipe (main inspection process):

Tube blank preparation and inspection → tube blank heating → perforation → tube rolling → waste tube reheating → diameter determination (reduction) → heat treatment → finished tube straightening → finishing → inspection (non-destructive, physical and chemical, Taiwan inspection) → storage

□

The main production process of cold-rolled (drawn) seamless steel pipe

Billet preparation → pickling lubrication → cold rolling (drawing) → heat treatment → straightening → finishing → inspection



Chongqing Zhengshen Stainless Steel Products Co.,Ltd.



+86 189 9647 2857



cqzhengshen@hotmail.com



pipesteels.com

Chenjiawan Industrial Park, Jieshi Town, Banan District, Chongqing, China