



## GB/T13793-1992 600mm Zinc Coating Pipe 12m Galvanised Steel Pipe

Our Product Introduction

for more products please visit us on [pipesteels.com](http://pipesteels.com)

### Basic Information

- Place of Origin: China
- Brand Name: Zhengshen
- Certification: ISO, GOST, CE
- Minimum Order Quantity: 1 T
- Price: USD500-800/Ton
- Delivery Time: 5-15 days
- Payment Terms: T/T, LC



### Product Specification

- Highlight: GB/T13793-1992 zinc coating pipe,  
600mm zinc coating pipe,  
12m galvanised steel pipe



### More Images



### Product Description

GB/T13793-1992 GB/T14291-2006 GB/T3091-1993 GB/T3092-1993 Galvanized Pipe

#### Feature:

The surface of the galvanized steel pipe is hot-dipped or electro-galvanized, which can increase the corrosion resistance and prolong the service life. Generally used for water, gas pipes, seamless pipes for steam pipes, oil pipelines, and pipes for oil and natural gas trunk lines. Agricultural irrigation faucets with pipes and pipes for sprinkler irrigation.

Our Product

Specification:

<b>OD</b>	10-600mm(round)
<b>Thickness</b>	1.2-30mm
<b>Length</b>	3-12m or as per customers' requirements
<b>Material</b>	Q195—Grade B, SS330, SPC, S185 Q215—Grade C, CS Type B, SS330, SPHC Q235—Grade D, SS400, S235JR, S235JO, S235J2 Q345—SS500, ST52
<b>Standard</b>	GB/T13793-1992, GB/T14291-2006, GB/T3091-1993, GB/T3092-1993, GB3640-88 BS1387/1985, ASTM A53/A36, EN39/EN10219, API 5L, GB/T9711.1-99 etc
<b>zinc coating</b>	pre-galvanized steel pipe: 60-150g/m2 hot dipped galvanized steel pipe: 200-400g/m2
<b>Application</b>	Widely used in structure, accessorize, construction, fluid transportation, machinery parts, the stress parts of the automobile tractor parts and so on
<b>Package</b>	1) Big OD: in bulk 2) Small OD: packed by steel strips 3) Plastic bags 4) According to the customer's requirement
<b>Delivery</b>	Normally 7-20 days after getting deposits or according to quantity
<b>Certification</b>	ISO 9001-2008 BV TUV
<b>Advantage</b>	1. reasonable price with excellent quality 2. abundant stock and prompt delivery 3. rich supply and export experience, sincere service

Chemical Composition & Mechanical Properties:

Grade	Chemical Composition					Mechanical Properties		
	C	Mn	Si	S	P	Yield	Tensile	Elongation
						Strength Mpa	Strength Mpa	-on %
Q195	0.06-0.12	0.25-0.50	≤0.30	≤0.045	≤0.05	≥195	315-430	≥33
Q215	0.09-0.15	0.25-0.55	≤0.30	≤0.05	≤0.045	≥215	335-450	≥27
Q235	0.12-0.20	0.30-0.67	≤0.30	≤0.045	≤0.04	≥235	375-500	≥26
Q345	≤0.20	1.00-1.60	≤0.55	≤0.04	≤0.04	≥345	470-630	≥22



Chongqing Zhengshen Stainless Steel Products Co., Ltd.



+86 189 9647 2857



cqzhengshen@hotmail.com



[pipesteels.com](http://pipesteels.com)

Chenjiawan Industrial Park, Jieshi Town, Banan District, Chongqing, China