

12 16 28 Inch SCH 40 10mm Custom Plastic Lined Steel Pipe

Basic Information

Place of Origin: ChinaBrand Name: ZhengshenCertification: ISO, GOST,CE

Minimum Order Quantity: 1 T

Price: USD400-600/Ton
Delivery Time: 5-15 days
Payment Terms: T/T, LC



Product Specification

Highlight: 28Inch Plastic Lined Steel Pipe,
 10mm Plastic Lined Steel Pipe,
 SCH 40 Steel Welded Pipe




More Images









Product Description

12 16 28 Inch SCH 40 10mm Custom Plastic Lined Steel Pipe

Feature:

Material: 45#, Q235, Q345, Q195, ST37, ST52, ST42, 10#-45#, Q195-Q345, ST35-ST52

Standard: API, ASTM, bs, DIN, GB, JIS, ASTM A53, ASTM A106, API 5L and so on, API 5L, ASTM A53-2007, BS 1387, BS EN10025, BS EN 39, BS, EN10219, DIN EN 10217-1-2005, DIN 2444, DIN EN 10025, GB/T 9711.1-1997, GB/T 3091-2001,

JIS G3444-2006

Outer diameter: 13.7 - 610 mm, DN8--DN600

Length: 6m/5.8m or customized

Advantages: Wholesale, Customisable, high quality

Seamless steel tubes are mainly used as petroleum geological drilling tubes, petrochemical cracking tubes, boiler tubes,

bearing tubes and high-precision structural steel tubes for automobiles, tractors and aviation.

Specification:

Place of Origin	Shandong, China	Processing Service		Welding, Punching, Cutting, Bending, Decoiling	
Brand Name	Zhengshen	Oiled or Non-oiled		contact	
Application	Fluid Pipe, Gas Pipe, Structure Pipe	Invoicing		by theoretical weight	
Alloy Or Not	Non-Alloy	Delivery Time		7days	
Section Shape	Round	Color		black	
Special Pipe	Thick Wall Pipe	Size		6-12m	
Outer Diameter	13.7 - 610 mm	Product name		Seamless Steel Pipe	
Thickness	1.3-15mm	Туре		Seamless Round Steel Pipe	
Standard	ASTM	Material		St52	
Length	12M, 6m, 6.4M, by customized, Customers' Requirements	Surface		Black Paint	
Certificate	API, ce, JIS, ISO9001	Keyword		Seamless Steel Pipe Tube	
Grade	Q195, Q235, Q345, #20	Shape		Round Pipe Tube	
Surface Treatment	Hot Rolled	Technology		ERW Hot Rolled	
Tolerance	±1%				
Commodity	LSAW steel pipe				
-	ERW/HFW LSAW/D	SAW S	SAW	RHS	
Outer diameter	1/8 - 26 inch 12 - 56 inc	12 - 56 inch (323.8 8 - 126 inch			40 x 20 mm -
	(10.3 - 740 mm) - 1,420mm	n) (219.1 - 3,200		mm)	1,000 x 800 mm
Wall thickness	0.4 - 16 mm 6.0 - 40 m				
Length	5.8 ~ 12.0 m or upon customers' requirements				
Standard	GB/T 3091, GB/T 13793, ASTM A252, ASTM A53, ASTM A500, EN 10210, EN 10219, API 5L,DIN 1626/1615, DIN 17120, etc.				
	SS400, Q235, Q345, Q460, A572 Gr.50, Gr.1/Gr.2/Gr.3, S235, S275, S355, Grade A/B, X42, X52, X60, X70, etc.				
Surface	Prime quality (bared, oiled, color paint, 3LPE, or other anti-corrosive treatment)				
Inspection	With Chemical Composition and Mechanical Properties Analysis; Dimensional and Visual Inspection, also with Nondestructive Inspection.				
Application	structure, electric power transmission tower projects, piling, water, oil & gas pipeline engineering, mechanical industry, municipal projects, roads and its auxiliary facilities, etc.				
Packing	Standard export, in bulk / bundles / nylon fabric bags with seaworthy packing; or according to customers' requestments.				

3



Chongqing Zhengshen Stainless Steel Products Co.,Ltd.

+86 189 9647 2857



cqzhengshen@hotmail.com



pipesteels.com

Chenjiawan Industrial Park, Jieshi Town, Banan District, Chongqing, China